

System Components

Active Loudspeaker Systems

200
watts

AS Q8

The concept behind the construction is to have a small sound system, tonally well balanced with excellent speech intelligibility, sufficient bass yet quick in response. A combination of bass reflex and band-pass supports the low ranges. Four power amplifiers driving four extended range 8" loudspeakers and a dome-tweeter, are hidden within this simple looking full-range system.

- 200 watts, dynamic control
- 2 x 8" woofer
- 2 x 8" twin-cone full-range speaker
- 1 x 1" dome-tweeter with horn
- two-way full-range system.
- bandpass/bassreflex construction
- 26 kg (57.32 lbs)

Inputs

inputs electronically balanced, 10 kOhm XLR-connector

Frequency

frequency response (1 watt @1m): -6dB: 65 Hz -20 kHz
axial sensitivity: 99 dB SPL, 1 watt @ 1m

crossover passive, 2,7 kHz, 12 dB/Oct.

Power

power amp 200 W / 4 ohms, dynamic control

analog signal processing subsonic filter, low distortion
RMS limiter

Speaker System

2 x 8" woofer
2 x 8" twin-cone full-range speaker
1 x 1" dome-tweeter with horn

Features

temperature protection, bass boost, ground lift,
mid-cut/treble boost

Accessories

softcover, K&M connector plate

Specifications

cabinet 15 mm (0.6") finnish birch plywood

finish waterbased acrylic, black spatter finish

dimensions 485 mm x 360 mm x 405 mm
(19.1" x 14.17" x 15.95") HxWxD

weight 26 kg (57.32 lbs)

Can be combined with

AS 550 D/sub

